



lunghezze standard gambo C standard stem lenght C
50 mm
100 mm
150 mm
200 mm
300 mm

modello model	Ø A
PSZ40PR	40 mm
PSZ50PR	52 mm
PSZ63PR	62 mm

Bi-metal pyrometer with rear stem and galvanized casing; not intended for specific uses but particularly suitable for measuring the temperature of fumes discharged by flues and boilers.

**CASING:** galvanized steel. The diameters available are listed in the table, other diameters on request.

**GLASS RETAINER:** nickel-plated steel.

**TRANSPARENT:** made of true glass, 2 millimetres thick.

**DIAL:** printed with UV inks on pre-painted aluminium. Customer's logo or special graphics on request.

**STANDARD GRADUATION:** 0/500 °C. Other graduations on request, including graduations in °F or with double scale °C/°F.

**MECHANISM:** bi-metal precision spiral (class 2 according to UNI EN 13190).

**STEM:** brass tube Ø 9. Standard rated length (C) on the table. Different stem lengths may be supplied on request. The pyrometer is usually supplied with a bare stem. On request it may be supplied with a sheath and/or lantern spring (see PSZ\_\_G models).

**NOTE:** several standard articles of PSZ63PR model are available from the SERVICE (please click on SERVICE LINE).