



modello model	Ø A
PST63P	62 mm
PST80P	80 mm
PST100P	99,4 mm

guaine standard standard pockets	L
1/2 x 5 cm	50 mm
1/2 x 10 cm	105 mm

Radial thermometer with stem and plastic casing (painted steel only for Ø 100); not intended for specific uses but particularly suitable for heating systems.

CASING: shockproof black ABS (painted steel only Ø 100). The diameters available are listed in the table. **STEM:** turned brass. Standard rated length (C) cm. 5 and 10. Different leg lengths may be supplied on request. **SHEATH:** The thermometer is usually supplied complete with a sheath. The sheath may be made of a bar of turned brass (rated length 5 cm) or with a turned brass coupling and a tubular copper leg (rated length 10 cm.). Sheaths with different measurements, threads and characteristics may be supplied on request. **LANTERN SPRING:** burnished steel. Its purpose is to hold the thermometer leg inside the sheath, or other housing, by friction. **TRANSPARENT:** in unbreakable methacrylate. **DIAL:** Pad-printed on stove-enamelled aluminium. Customer's logo or special graphics on request. **MECHANISM:** sensitive precision element with liquid expansion. **STANDARD GRADUATIONS:** -30/+50 0/60 0/120 °C. Other graduations on request, including graduations in °F or with double scale °C/°F. **NOTE:** the standard models are available from the SERVICE dept. (See SERVICE PRICE LIST).